Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name of | or trade mark: | V-TAC |
|--------------------|----------------|-------|
|--------------------|----------------|-------|

Supplier's address: V-TAC Europe Ltd., bul. Rozhen 41, Sofia, BG

Model identifier: 10564

| Tvi | рe | of | lig | ht | SO | urce | : |
|-------|----|----|-----|----|----|------|---|
| . , , | | • | о | | - | | • |

imal

ing

Outer dimen-

sions without

separate con-

trol gear, light-

control

Height

Width

Depth

| Lighting technology used: | LED | Non-directional or directional: | NDLS |
|--|---------------------------|--|-------|
| Light source cap-type | L/N/G CON- | | |
| (or other electric interface) | NECTION | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | No |
| | Product para | meters | ı |
| Parameter | Value | Parameter | Value |
| | General product p | parameters: | |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | 15 | Energy efficiency class | E |
| Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 1 900 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000 |
| On-mode power (P _{on}), ex- pressed in W | 15,0 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second dec- | - | Colour rendering in- dex, rounded to the nearest integer, or | 90 |

164

165

160

the range of CRI-val-

in the

ues that can be set

Spectral power dis-

range 250 nm to 800

nm, at full-load

tribution

See image

in last page

| parts and non- lighting con- trol parts, if any (millime- tre) | | | | | |
|--|------|------------------------------|-------|--|--|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | | |
| | | Chromaticity coordi- | 0,440 | | |
| | | nates (x and y) | 0,403 | | |
| Parameters for LED and OLED light sources: | | | | | |
| R9 colour rendering index value | 80 | Survival factor | 0,90 | | |
| the lumen maintenance factor | 0,96 | | | | |

(a)'-': not applicable; (b)'-': not applicable;

